

FORM-PTO-1390
(Rev. 9-2001)

U S DEPARTMENT OF COMMERCE PATENT AND TRADEMARK OFFICE

ATTORNEY'S DOCKET NUMBER

**TRANSMITTAL LETTER TO THE UNITED STATES
DESIGNATED/ELECTED OFFICE (DO/EO/US)
CONCERNING A FILING UNDER 35 U.S.C. 371**

003300-896

U S APPLICATION NO. (If known, see 37 C.F.R. 1.5)

unassigned **10/031410**

INTERNATIONAL APPLICATION NO.
PCT/SE00/01484

INTERNATIONAL FILING DATE
13 July 2000

PRIORITY DATE CLAIMED
30 July 1999

TITLE OF INVENTION

A METHOD FOR SELECTIVE ELECTROFUSION OF AT LEAST TWO FUSION PARTNERS HAVING CELL-LIKE MEMBRANES

APPLICANT(S) FOR DO/EO/US

PETER ERIKSSON, DANIEL T. CHIU, ALEXANDER MOSCHO, OWE ORWAR and RICHARD N. ZARE

Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information:

It is contemplated that this Application be prosecuted while using Claims 1 to 30 that were submitted on September 24, 2001 during the international phase of examination as further amended in the Preliminary Amendment filed herewith.

1. ☒ This is a **FIRST** submission of items concerning a filing under 35 U.S.C. 371.
2. ☐ This is a **SECOND** or **SUBSEQUENT** submission of items concerning a filing under 35 U.S.C. 371.
3. ☒ This is an express request to begin national examination procedures (35 U.S.C. 371(f)). The submission must include items (5), (6), (9) and (21) indicated below.
4. ☐ The US has been elected by the expiration of 19 months from the priority date (Article 31).
5. ☒ A copy of the International Application as filed (35 U.S.C. 371(c)(2))
 - a. ☒ is attached hereto (required only if not communicated by the International Bureau).
 - b. ☒ has been communicated by the International Bureau.
 - c. ☐ is not required, as the application was filed in the United States Receiving Office (RO/US).
6. ☐ An English language translation of the International Application as filed (35 U.S.C. 371(c)(2))
 - a. ☐ is attached hereto.
 - b. ☐ has been previously submitted under 35 U.S.C. 154(d)(4).
7. ☒ Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371(c)(3))
 - a. ☐ are attached hereto (required only if not communicated by the International Bureau).
 - b. ☐ have been communicated by the International Bureau.
 - c. ☐ have not been made; however, the time limit for making such amendments has NOT expired.
 - d. ☒ have not been made and will not be made.
8. ☐ An English language translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)).
9. ☒ An oath or declaration of the inventor(s) (35 U.S.C. 371(c)(4)). (Signed Declaration will follow.)
10. ☐ An English language translation of the annexes to the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371(c)(5)).

Items 11 to 20 below concern document(s) or information included:

11. ☒ An Information Disclosure Statement under 37 CFR 1.97 and 1.98.
12. ☐ An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included.
13. ☒ A **FIRST** preliminary amendment.
14. ☐ A **SECOND** or **SUBSEQUENT** preliminary amendment.
15. ☐ A substitute specification.
16. ☐ A change of power of attorney and/or address letter.
17. ☐ A computer-readable form of the sequence listing in accordance with PCT Rule 13ter.2 and 35 U.S.C. 1.821 - 1.825.
18. ☐ A second copy of the published international application under 35 U.S.C. 154(d)(4).
19. ☐ A second copy of the English language translation of the international application under 35 U.S.C. 154(d)(4).
20. ☐ Other items or information:

Transmittal of Formal Drawings.

A certified copy of Swedish Application No. 9902817-7 filed July 30 1999 was submitted during the international phase of examination. Thus the claim for priority has been perfected.

U.S. APPLICATION NO. (If known, see 37 C.F.R. 1.5) Unassigned		INTERNATIONAL APPLICATION NO. PCT/SE00/01484		ATTORNEY'S DOCKET NUMBER 003300-896	
---	--	--	--	---	--

21. ☒ The following fees are submitted:

Basic National Fee (37 CFR 1.492(a)(1)-(5)):

Neither international preliminary examination fee (37 CFR 1.482) nor international search fee (37 CFR 1.445(a)(2)) paid to USPTO and International Search Report not prepared by the EPO or JPO \$1,040.00 (960)

International preliminary examination fee (37 CFR 1.482) not paid to USPTO but International Search Report prepared by the EPO or JPO \$890.00 (970)

International preliminary examination fee (37 CFR 1.482) not paid to USPTO but international search fee (37 CFR 1.445(a)(2)) paid to USPTO \$740.00 (958)

International preliminary examination fee (37 CFR 1.482) paid to USPTO but all claims did not satisfy provisions of PCT Article 33(1)-(4) \$710.00 (956)

International preliminary examination fee (37 CFR 1.482) paid to USPTO and all claims satisfied provisions of PCT Article 33(1)-(4) \$100.00 (962)

ENTER APPROPRIATE BASIC FEE AMOUNT =

Surcharge of **\$130.00 (154)** for furnishing the oath or declaration later than 20 ☐ 30 ☐ months from the earliest claimed priority date (37 CFR 1.492(e)).

Claims	Number Filed	Number Extra	Rate	
Total Claims	33 -20 =	13	X\$18.00 (966)	\$ 234.00
Independent Claims	1 -3 =	0	X\$84.00 (964)	\$ --
Multiple dependent claim(s) (if applicable)			+ \$280.00 (968)	\$ --
TOTAL OF ABOVE CALCULATIONS =				\$ 1,274.00
Reduction for 1/2 for filing by small entity, if applicable (see below).				+ \$ 637.00
SUBTOTAL =				\$ 637.00
Processing fee of \$130.00 (156) for furnishing the English translation later than 20 <input type="checkbox"/> 30 <input type="checkbox"/> months from the earliest claimed priority date (37 CFR 1.492(f)).				+ \$ --
TOTAL NATIONAL FEE =				\$ 637.00
Fee for recording the enclosed assignment (37 CFR 1.21(h)). The assignment must be accompanied by an appropriate cover sheet (37 CFR 3.28, 3.31). \$40.00 (581) per property				+ \$ --
TOTAL FEES ENCLOSED =				\$ 637.00
				Amount to be refunded: \$
				charged: \$

PTO USE ONLY

a. ☒ Small entity status is hereby claimed.

b. ☒ A check in the amount of \$ 637.00 to cover the above fees is enclosed.

c. ☐ Please charge my Deposit Account No. 02-4800 in the amount of \$ _____ to cover the above fees. A duplicate copy of this sheet is enclosed.

d. ☒ The Commissioner is hereby authorized to charge any additional fees which may be required, or credit any overpayment to Deposit Account No. 02-4800. A duplicate copy of this sheet is enclosed.

NOTE: Where an appropriate time limit under 37 CFR 1.494 or 1.495 has not been met, a petition to revive (37 CFR 1.137(a) or (b)) must be filed and granted to restore the application to pending status.

SEND ALL CORRESPONDENCE TO:

Benton S. Duffett, Jr.
 BURNS, DOANE, SWECKER & MATHIS, L.L.P.
 P.O. Box 1404
 Alexandria, Virginia 22313-1404
 (703) 836-6620

 SIGNATURE
Benton S. Duffett, Jr.
 NAME
22,030
 REGISTRATION NUMBER
January 18, 2002
 DATE

Patent
Attorney's Docket No. 003300-896

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Patent Application of)	
)	
PETER ERIKSSON et al.)	BOX PCT
)	
Application No.: (unassigned))	Attention: DO/EO/US
)	
Filed: January 18, 2002)	Group Art Unit: (unassigned)
)	
For: A METHOD FOR SELECTIVE)	Examiner: (unassigned)
ELECTROFUSION OF AT LEAST)	
TWO FUSION PARTNERS HAVING)	
CELL-LIKE MEMBRANES)	

TRANSMITTAL OF FORMAL DRAWINGS

Assistant Commissioner for Patents
Washington, D.C. 20231

Sir:

Applicants provide five (5) sheets of formal drawings (i.e., Figs. 1 to 5).

The examination and allowance of the application are respectfully requested.

Respectfully submitted,

BURNS, DOANE, SWECKER & MATHIS, L.L.P.

By: Benton S. Duffett, Jr.
Benton S. Duffett, Jr.
Registration No. 22,030

P.O. Box 1404
Alexandria, Virginia 22313-1404
(703) 836-6620

Filed: January 18, 2002

1/5




Fig. 1

2/5




Fig. 2

3/5




Fig. 3

10/031410

4/5




Fig. 4

5/5




Fig. 5

Patent
Attorney's Docket No. 003300-896

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Patent Application of)	
)	
PETER ERIKSSON et al.)	BOX PCT
)	
Application No.: (unassigned))	Attention: DO/EO/US
)	
Filed: January 18, 2002)	Group Art Unit: (unassigned)
)	
For: A METHOD FOR SELECTIVE)	Examiner: (unassigned)
ELECTROFUSION OF AT LEAST)	
TWO FUSION PARTNERS HAVING)	
CELL-LIKE MEMBRANES)	

PRELIMINARY AMENDMENT

Assistant Commissioner for Patents
Washington, D.C. 20231

Sir:

This is a national phase filing of International Application No. PCT/SE00/01484,
filed July 13, 2000.

It is contemplated that this application be prosecuted while using Claims 1 to 30 that
were submitted on September 24, 2001 during the international phase of examination as
further amended herein.

Please amend the application as indicated.

IN THE ABSTRACT:

Please add the Abstract of the Disclosure that is provided on a separate sheet.

IN THE CLAIMS:

Kindly replace Claims 4 to 9, and 11 to 30 as follows:

4. (Amended) A method according to claim 1, wherein one electrode movably mounted on a microchip is used to provide the electrical field in step B.

5. (Amended) A method according to claim 1, wherein several electrodes movably mounted on a microchip are used to provide the electrical field in step B.

6. (Amended) A method according to claim 4, wherein one electrode(s) is (are) movably mounted on a microchip of a suitable design for combinatorial synthesis of fusion products.

7. (Amended) A method according to claim 2, wherein at least one microelectrode is hollow, and sufficiently small to permit the selective fusion of two fusion partners.

8. (Amended) A method according to claim 2, wherein at least one microelectrode that is hollow, electrolyte-filled, and sufficiently small to permit the selective fusion of two fusion partners, is used to provide the electrical field in step B, and said microelectrode is also used to deliver fusion partners or chemical agents by electroendoosmosis, electrophoresis, or by Poiseuille flow.

9. (Amended) A method according to claim 2, wherein the outer diameter of said electrode(s) is sufficiently small to permit the selective fusion of said at least two fusion partners without affecting nearby structures, such as cells, liposomes, and proteoliposomes.

11. (Amended) A method according to claim 2, wherein at least one electrode is used for delivery of at least one fusion partner to the fusion site.

12. (Amended) A method according to claim 2, wherein step A is performed by use of the electrodes.

13. (Amended) A method according to claim 1, wherein step A is performed by use of optical trapping.

14. (Amended) A method according to claim 1, wherein step A is performed by use of micropipettes.

15. (Amended) A method according to claim 1, wherein at least one of the fusion partners is a cell, and the other fusion partner(s) independently is (are) selected from the group consisting of a single cell, a liposome, a proteoliposome, a synthetic vesicle, an egg cell, an enucleated egg cell, a sperm cell at any development stage and a plant protoplast.

16. (Amended) A method according to claim 1, wherein at least one of the fusion partners is constituted by a multiple of a structure selected from the group consisting of a single cell, a liposome, a proteoliposome, a synthetic vesicle, an egg cell, an enucleated egg cell, a sperm cell at any development stage and a plant protoplast.

17. (Amended) A method according to claim 1, wherein the fusion partners are provided in a buffer prior to step B.

18. (Amended) A method according to claim 1, wherein at least one of the fusion partners has been immobilized prior to step A.

19. (Amended) A method according to claim 1, wherein one of the fusion partners is part of a cellular network.

20. (Amended) A method according to claim 1, wherein at least one of the fusion partners has been electroporated in a buffer prior to step A.

21. (Amended) A method according to claim 1, wherein at least one of the fusion partners has been exposed to a dielectrophoretic field in a buffer prior to step A.

22. (Amended) A method according to claim 1, wherein at least one of the fusion partners has been treated by a fusogenic or other agent that promotes close cell-cell contacts.

23. (Amended) A method for conducting in vitro-fertilization comprising using the method according to claim 1.

24. (Amended) A method for conducting cloning, excluding human cloning comprising using the method according to claim 1.

25. (Amended) A method for creation of hybridomas comprising using the method according to claim 1.

26. (Amended) A method for manipulation of the composition of a cellular membrane comprising using the method according to claim 1.

27. (Amended) A method for the delivery of a well-defined volume of a substance to a cell comprising using the method according to claim 1.

28. (Amended) A method for the delivery of a pharmaceutically active substance to a cell comprising using the method according to claim 1.

29. (Amended) A method for the treatment of a tumor comprising using the method according to claim 1.

30. (Amended) A method for the treatment of chronic neurodegenerative diseases, such as Parkinson's disease and Alzheimer's disease comprising using the method according to claim 1.

Please add the following new Claims 31 to 33.

31. (New) A method according to claim 2, wherein one electrode movably mounted on a microchip is used to provide the electrical field in step B.

32. (New) A method according to claim 3, wherein several electrodes movably mounted on a microchip are used to provide the electrical field in step B.

33. (New) A method according to claim 5, wherein one electrode(s) is (are) movably mounted on a microchip of a suitable design for combinatorial synthesis of fusion products.

Application No. (unassigned)
Attorney's Docket No. 003300-896
Page 7

REMARKS

The present Amendment modifies the claim format only and eliminates the use of multiple dependency.

An Information Disclosure Statement and Transmittal of Formal Drawings are being filed concurrently herewith.

The examination and allowance of the application are respectfully requested.

Respectfully submitted,

BURNS, DOANE, SWECKER & MATHIS, L.L.P.

By: Benton S. Duffett, Jr.
Benton S. Duffett, Jr.
Registration No. 22,030

P.O. Box 1404
Alexandria, Virginia 22313-1404
(703) 836-6620

Filed: January 18, 2002

Application No. (unassigned)
Attorney's Docket No. 003300-896
Mark-up of Claims - Page 1

Attachment to Preliminary Amendment dated January 18, 2002

4. (Amended) A method according to claim 1 [or 2], wherein one electrode movably mounted on a microchip is used to provide the electrical field in step B.
5. (Amended) A method according to claim 1 [or 3], wherein several electrodes movably mounted on a microchip are used to provide the electrical field in step B.
6. (Amended) A method according to claim 4 [or 5], wherein one electrode(s) is (are) movably mounted on a microchip of a suitable design for combinatorial synthesis of fusion products.
7. (Amended) A method according to [any one of the claims 2-6] claim 2, wherein at least one microelectrode is hollow, and sufficiently small to permit the selective fusion of two fusion partners.
8. (Amended) A method according to claim [2-7] 2, wherein at least one microelectrode that is hollow, electrolyte-filled, and sufficiently small to permit the selective fusion of two fusion partners, is used to provide the electrical field in step B, and said microelectrode is also used to deliver fusion partners or chemical agents by electroendoosmosis, electrophoresis, or by Poiseuille flow.

Application No. (unassigned)
Attorney's Docket No. 003300-896
Mark-up of Claims - Page 2

Attachment to Preliminary Amendment dated January 18, 2002

9. (Amended) A method according to [any one of the claims 2-8] claim 2, wherein the outer diameter of said electrode(s) is sufficiently small to permit the selective fusion of said at least two fusion partners without affecting nearby structures, such as cells, liposomes, and proteoliposomes.

11. (Amended) A method according to [any one of the claims 2-10] claim 2, wherein at least [on] one electrode is used for delivery of at least on fusion partner to the fusion site.

12. (Amended) A method according to [any one of the claims 2-11] claim 2, wherein step A is performed by use of the electrodes.

13. (Amended) A method according to [any one of the claims 1-11] claim 1, wherein step A is performed by use of optical trapping.

14. (Amended) A method according to [any one of the claims 1-11] claim 1, wherein step A is performed by use of micropipettes.

15. (Amended) A method according to [any one of the claims 1-11] claim 1, wherein at least one of the fusion partners is a cell, and the other fusion partner(s) independently is (are) selected from the group consisting of a single cell, a liposome, a

Application No. (unassigned)
Attorney's Docket No. 003300-896
Mark-up of Claims - Page 3

Attachment to Preliminary Amendment dated January 18, 2002

proteoliposome, a synthetic vesicle, an egg cell, an enucleated egg cell, a sperm cell at any development stage and a plant protoplast.

16. (Amended) A method according to [any one of the claims 1-14] claim 1, wherein at least one of the fusion partners is constituted by a multiple of a structure selected from the group consisting of a single cell, a liposome, a proteoliposome, a synthetic vesicle, an egg cell, an enucleated egg cell, a sperm cell at any development stage and a plant protoplast.

17. (Amended) A method according to [any one of the claims 1-16] claim 1, wherein the fusion partners are provided in a buffer prior to step B.

18. (Amended) A method according to [any one of the claims 1-17] claim 1, wherein at least one of the fusion partners has been immobilized prior to step A.

19. (Amended) A method according to [any one of the claims 1-18] claim 1, wherein one of the fusion partners is part of a cellular network.

20. (Amended) A method according to [any one of the claims 1-19] claim 1, wherein at least one of the [Fusion Partners] fusion partners has been electroporated in a buffer prior to step A.

Application No. (unassigned)
Attorney's Docket No. 003300-896
Mark-up of Claims - Page 4

Attachment to Preliminary Amendment dated January 18, 2002

21. (Amended) A method according to [any one of the claims 1-20] claim 1, wherein at least one of the [Fusion Partners] fusion partners has been exposed to a dielectrophoretic field in a buffer prior to step A.

22. (Amended) A method according to [any one of the claims 1-21] claim 1, wherein at least one of the [Fusion Partners] fusion partners has been treated by a fusogenic or other agent that promotes close cell-cell contacts.

23. (Amended) [Use of a method according to any one of the claims 1-21 in] A method for conducting in vitro-fertilization comprising using the method according to claim 1.

24. (Amended) [Use of a method according to any one of the claims 1-22 in] A method for conducting cloning, excluding human cloning comprising using the method according to claim 1.

25. (Amended) [Use of a method according to any one of the claims 1-22] A method for creation of hybridomas comprising using the method according to claim 1.

Application No. (unassigned)
Attorney's Docket No. 003300-896
Mark-up of Claims - Page 5

Attachment to Preliminary Amendment dated January 18, 2002

26. (Amended) [Use of a method according to any one of the claims 1-22] A method for manipulation of the composition of a cellular membrane comprising using the method according to claim 1.

27. (Amended) [Use of a method according to any one of the claims 1-22] A method for the delivery of a well-defined volume of a substance to a cell comprising using the method according to claim 1.

28. (Amended) [Use of a method according to any one of the claims 1-22] A method for the delivery of a pharmaceutically active substance to a cell comprising using the method according to claim 1.

29. (Amended) [Use of a method according to any one of the claims 1-22 in] A method for the treatment of a tumor comprising using the method according to claim 1.

30. (Amended) [Use of a method according to any one of the claims 1-22 in] A method for the treatment of chronic neurodegenerative diseases, such as Parkinson's disease and Alzheimer's disease comprising using the method according to claim 1.

Abstract of the Disclosure

Disclosed is a method for selective electrofusion of at least two fusion partners having cell-like membranes and cellular or subcellular dimensions, comprising the following steps: A) the fusion partners are brought into contact with each other and B) an electrical field of a strength sufficient to obtain fusion and highly focused on the fusion partners is applied. The fusion partners are independently selected from the group consisting of a single cell, a liposome, a proteoliposome, a synthetic vesicle, an egg cell, an enucleated egg cell, a sperm cell at any development stage and a plant protoplast.

A METHOD FOR SELECTIVE ELECTROFUSION OF AT LEAST TWO
FUSION PARTNERS HAVING CELL-LIKE MEMBRANES

Field of the invention

The present invention relates to a method for selective electrofusion of at least two fusion partners having cell-like membranes.

5

Background of the invention

Electrofusion has developed into an extremely efficient method for the fusion of mammalian cells, mainly because of its mild conditions, which result in a high
10 number of viable fusion products [see e.g. White, K. L. 1995, Electrofusion of mammalian cells, Methods in Molecular Biology, 48, 283-293]. The application of an electrical field over phospholipid bilayer membranes induces pore formation when the applied potential reaches
15 or exceeds the membrane breakdown potential. Consequently, electro-permeabilization techniques has been used in a wide variety of biological experiments, like electrofusion for the creation of hybridomas and new cell lines [see e.g. Zimmermann, U., et al., 1985, Electrofu-
20 sion: a novel hybridization technique, Adv. Biotechnol. Proc. 4, 79-150; Neil, G. A. et al., 1993. Electrofusion, Methods in Enzymology, 220, 174-196; Glassy, M. 1988, Product review: Creating hybridomas by electrofusion, Nature, 333, 579-580], in vitro fertilization [see e.g.
25 Ogura, A. et al., 1995, Spermatids as male gametes. Reprod. Fertil. Dev., 7, 155-159], cloning experiments [see e.g. Van Stekelenburg-Hamers, A. E. P., et al., 1993, Nuclear transfer and electrofusion in bovine in vitro-matured / in vitro-fertilized embryos: effect of media
30 and electrical fusion parameters, Mol. Reprod. Dev., 36, 307-312], electroporation of cells for introduction of cell-impermeant solutes [see e.g. Electroporation: a general phenomenon for manipulating cells and tissues, J.

Cell. Biochem., 51: 426-435; Li, H., et al., 1997, Transfection of rat brain cells by electroporation, J. Neurosci. Methods, 75, 29-32; Lundqvist, J. A., et al., 1998, Altering the biochemical state of individual cultured
5 cells and organelles with ultramicroelectrodes, Proc. Natl. Acad. Sci. USA, 95, 10356-10360], and electroinsertion for the addition of membrane-associated macromolecules, including proteins [see e.g. Mouneimne, Y., et al., 1989, Electro-insertion of xeno-glycophorin into the
10 red blood cell membrane, Biochem. Biophys. Res. Com. 159, 34-40]. Applications of *in vivo* electrofusion include the incorporation of gonococcal attachment receptors from human HL60 cells to rabbit corneal epithelial tissue as a viable model of human-specific pathogens [see e.g. Heller, R., et al., 1990, Transfer of human membrane surface
15 components by incorporating human cells into intact animal tissue by cell-tissue electrofusion *in vivo*, Biochim. Biophys. Acta, 1024, 185-188].

Electric-field-induced fusion is widely employed in
20 biomedical research for a population of cells in suspension. Cells are first brought into contact by dielectrophoresis through the application of a low-amplitude, high-frequency AC field and subsequently a fraction of the cells are fused by a strong and short DC pulse. Bulk
25 electrofusion of large quantities of cells is useful for creating and selecting new cell lines, but cannot be applied to fuse single cells with high precision. This leads to unwanted fusion between cells from the same cell-line, as well as the wanted fusion between cells
30 from different cell lines. Furthermore, bulk electrofusions do not allow the control over the number of cells that are to be fused together, which leads to unfavorable ratios of dinuclear-to-multinuclear fusion products.

Summary of the invention

It is often desirable to selectively and controllably alter the biochemical, and genetic properties of single cells. To address this challenge and to overcome the shortcomings of bulk electrofusion, the inventors of the present invention have developed a technique to fuse together a single pair of cells at a time. The ability to controllably fuse together single cells represents a technique by which the long-term genetic identity and behavior of a selected cell can be precisely manipulated, and opens up new possibilities to create combinatorial libraries of hybrid, and cloned cells. In combination with a powerful measurement and imaging technique, the genetic and biochemical nature of single cells can be studied in detail.

Alteration of cellular properties can also be achieved by fusing together a synthetic phospholipid vesicle with the desired vesicular content and membrane compositions to a target cell. This technique can be used to alter the contents and membrane properties of single cells. It is, for example, possible to introduce a membrane protein reconstituted in liposomes into the cell plasma membrane. This ability to selectively transform the membrane composition of single cells is anticipated to have useful biological applications, such as the introduction of surface receptors for the screening of potential ligands and related pharmacological compounds.

Thus, the present invention provides a novel method for the selective electrofusion of cellular structures, such as cells and liposomes. This method offers the advantage of cell-selection, fusion of adherent cell structures with a high spatial resolution, giving the possibility to create complex cellular networks. As electrofusion is a mild method, this miniaturized version can, for example, be used for cloning on the single cell level and for *in vitro* fertilization. For cloning experiments in particular, the shortcomings of bulk electrofusion is

overcome with the present technique as it offers complete control over the fusion process and any doubts to the identity of the somatic cells needs not to be raised. Also, this method, preferentially in combination with micro-
5 machined chip technology, can be used to create screening libraries of cloned cells or hybrid cells.

The characterizing features of the invention will be evident from the following description and the appended claims.

10

Brief description of the drawings

In the description and the examples below, reference is made to the accompanying drawings on which:

Fig. 1 is a schematic drawing showing the experimental set up. Cells 1, 2 are added from suspension to a microscope coverslip 3 mounted in a polycarbonate holder. The cells are either prealigned using optical trapping (MOPA laser 4) or simply by pushing them together with the microelectrodes 5, 6 controlled by high-graduation
15 micromanipulators 7. For fluorescence imaging and optical trapping, two collinear laser beams are sent into the microscope objective 9; an argon ion laser 10 (black, thin arrows) is used to excite fluorescein, and a MOPA diode laser 4 (black thick arrows) is used for optical trap-
20 ping. The resulting fluorescence and bright field images are directed to a CCD camera 11.

Figs. 2 A - C show the alignment of a liposome with a selected cell using a microelectrode, and Figs. 2 D - E show six fluorescein-containing (10 μ M) liposomes brought
30 into contact with a cell. As shown in Fig. 2 G, no resulting background fluorescence is detected, and this illustrates that selective delivery of a drug to the surface (electropermeabilization of the liposome), or interior (electrofusion between the cell and liposome) is
35 possible.

Figs. 3 A - D show a cell-cell fusion sequence. Fig. 3 A shows PC12 cells during dielectrophoresis (0.3 - 3

kV/cm, 2 MHz). Fig. 3 B illustrates initiation of the fusion by the last fusion pulse (6 pulses of 1 ms duration per each, 3 kV/cm), this can be seen by a broader and flatter contact zone between the cells. Fig. 3 C (~1 minute after the fusion pulses) and Fig. 3 D (~2 minutes after the fusion pulses) show the subsequent broadening of the fusion area between the cells, indicating complete fusion.

Figs. 4 A - C show Bright-field images taken before (Fig. 4 A), during (Fig. 4 B), and after (Fig. 4 C) electrofusion (8 kV/cm, 4 ms) of a phosphatidylcholine (PC) liposome (left) with a COS 7 cell (right). Figs. 4 D - E show fusion between a NG-108 cell (protease-treated for 30 minutes) and a PC liposome with incorporated γ -glutamyltransferase (γ -GT). In Fig. 4 E it is seen how the microelectrode is gently pulled away from the cell, and the liposome (which is attached to the microelectrode) is stretched but does not detach from the cell.

Fig. 5 illustrates an example of a clinical application of the method according to the invention, wherein single or multiple cells in the brain are electrofused to incorporate the content of the other fusion partner. The fusion partner is delivered via a hollow electrode. The electrode is positioned using a stereotactic device, represented in the figure by the Cartesian co-ordinate system, and stereotactic micropositioners.

Detailed description of the invention

The invention relates to a method for selective electrofusion of at least two fusion partners having cell-like membranes, comprising the following steps: A) the fusion partners are brought into contact with each other, and B) an electrical field of a strength sufficient to obtain fusion and highly focused on the fusion partners is applied.

Said at least two fusion partners having cell-like membranes are preferably structures of cellular or sub-

cellular dimensions. The expression "structure of cellular or subcellular dimensions" relates in particular to biological structures such as independent cells and smaller structures, but it also relates to similar artificial structures. Thus, the fusion partners may be, independently of each other, a single cell, a liposome, a proteoliposome, a synthetic vesicle, a plant protoplast, an egg cell, a sperm or spermatid, and an enucleated egg cell.

10 As stated above, the fusion partners are brought into contact with each other. This means either that they are placed so that the outer surfaces of the fusion partners are touching, or that the fusion partners are placed at a very small distance from each other.

15 In most cases the method according to the invention is used for fusion of two fusion partners, below denoted Fusion Partner I and Fusion Partner II, however it, is also possible to fuse more than one fusion partner. In some cases it is especially interesting to fuse more than
20 two partners, for example, to create multinuclear cells with more than two nuclei, or when one of the partners is of much larger dimensions than the others. An example of this is when one wishes to introduce a substance contained in vesicles into a cell. In this case Fusion Partner I is the cell and Fusion Partner II is several of the
25 smaller vesicles.

Furthermore, it is possible to repeat the method according to the invention one or several times, so that a new fusion partner is fused to two already fused fusion
30 partners. This is of particular importance when combinatorial libraries of cloned cells and hybrid cells are created.

When Fusion Partner I is a cell and Fusion Partner II is a single liposome, the fusion of them allows both
35 the introduction of the liposomal content into the cell interior as well as the addition of lipids and membrane proteins from the liposome membrane into the cell sur-

face. This cell-liposome fusion represents a novel approach to the manipulation of the membrane contents and surface properties of single cells.

To fuse Fusion Partner I, such as a cell, a liposome
5 or another similar structure, to Fusion Partner II, such as a cell, liposome or similar structure, it is necessary to place the two fusion partners next to each other, i.e. in contact with each other. The fact that the two fusion partners are placed next to each other before fusion
10 makes it possible to avoid dielectrophoresis, which traditionally is used for the creation of close contact between cells. However, dielectrophoresis can be used successfully in combination with this invention to create and establish close cell-cell contacts before the dc-
15 field fusion pulse is applied. Mechanically, close contact between the fusion partners can be done in any suitable way. Individual manipulation of the two fusion partners for alignment facilitates this alignment. Using, for example, optical trapping with highly focused laser
20 beams, individual cells, as well as other biological structures, including organelles of small dimension, can be manipulated and moved at will [this has been described previously, see e.g. Jaroszeski, M. J., et al., 1994. Mechanically facilitated cell-cell electrofusion, Biophys.
25 J., 67, 1574-1581; Uchida, M., et al., 1995, Whole-cell manipulation by optical trapping, Curr. Biol., 5, 380-382; Chiu, D. T., et al., 1998, Probing single secretory vesicles with capillary electrophoresis, Science, 279: 1190-1193]. When electrodes are used for positioning of
30 the fusion partners, as described below, it is possible to align the two fusion partners by adjusting their positions by moving them with the tips of the electrodes. In order to move the electrodes it may be advantageous to use a microscope, at least one micropositioner and/or a
35 stereotactic device. To further facilitate the positioning of the two fusion partners, it may be advantageous to immobilize one of the fusion partners prior to performing

step A. When electrodes are used, this may, for example, be done by reversibly adhere at least one of the fusion partners to at least one of the microelectrodes. In some cases it may be advantageous to use dielectrophoresis, as pretreatment of the two aligned cells, before fusion. This can be done by connecting an ac-field sweep function generator to the electrodes.

The electrical field may be obtained by use of a low-voltage or high-voltage pulse-generator depending on the electrodes used, and other experimental parameters. The voltage generator is used to produce an electric field strength sufficient to result in fusion between the two fusion partners, approximately 0.1-10 kV/cm, for durations of 10 μ s to several seconds. The voltage measured at the membrane of the fusion partners should be between a few hundred millivolts to several volts, preferably around 1.5V. In the case of multiple-voltage-pulse protocols, we have found that a pulse repetition rate of approximately 1 Hz, to be suitable, however, other repetition rates might work well. For longer pulse-application durations, correspondingly, repetition rates of a lower frequency should be used. In any event, the length and the strength of the pulses depend on the size of the partners to be fused. Preferably, the fusion pulses have a rectangular waveform, but other waveforms works as well, including various ac-field pulse protocols. For dielectrophoresis, the sweep function generator preferably generates a alternating field, sinus-wave form, of field strengths between 100 V/cm - 5 kV/cm, 100 Hz - 2 MHz.

The electrical field used in step B to obtain fusion should be highly focused in order to avoid affecting any surrounding structures and to obtain the advantages of the present invention. To focus the electrical field it is preferable to provide the electrical field by use of one or two microelectrodes positioned close to the two fusion partners, i.e. 0 - 10 μ m, preferably 0 - 5 μ m, from the cellular membrane. In the case of using a single

electrode, this electrode is preferably, biased at a positive potential (anode) and work against a grounded cell preparation. According to the invention the micro-electrodes are preferably electrodes of cellular to sub-cellular dimensions. Preferably the outer dimension of the ends of the electrodes positioned closest to the fusion partners is from a few nanometers to ~100 micrometers, more preferably 5-30 micrometers and most preferably approximately 20 μm . The electrodes can be made of a solid electrically conducting material, or they can be hollow for delivery of fusion partners or chemical agents of choice. The electrodes can be made from different materials. A special type of electrodes are hollow and made from fused silica capillaries of a type that frequently is used for capillary electrophoresis and gas chromatographic separations. These capillaries are typically one-to-one hundred micrometers in inner diameter, and five-to-four hundred micrometers in outer diameter, with lengths between a few millimeters up to one meter. For cell fusion applications, these electrodes are filled with an electrolyte, preferably a physiological buffer solution. When a potential sufficient to cause cell-fusion is applied over the capillary, electroosmotic bulk flow is induced in the capillary, which in combination with Pouiseille flow (gravitational flow in capillaries) can be used to efficiently transfer materials to the fusion partners. Such hollow narrow-bore fused silica capillaries have the additional advantage that components added to the inlet end can be fractionated based on their charge-to-frictional drag ratio. This characteristic feature of the system can be used to, for example, investigate the effect of various fractionated components on cell fusion.

Furthermore, it is preferred to provide the two fusion partners in an electrofusion buffer prior to step B.

In order to facilitate the fusion, it may be advantageous to pre-electroporate at least one of the fusion partners before step A is performed.

When one (or both) of the fusion partners is a cell,
5 it may be part of a cellular network or a tissue, for example, in order to study cellular networks where, for example, the alteration of the biochemical identity of a selected cell can have profound effects on the behavior of the entire network.

10 A setup suitable for performing the method according to the invention is illustrated in Fig. 1. In this figure the two fusion partners 1, 2 both are cells. The cells to be fused are added from a suspension to a microscope coverslip 3 mounted in a polycarbonate holder.

15 The cells are either prealigned using optical trapping (MOPA laser 4) or simply by pushing them together with the microelectrodes 5, 6 controlled by high-graduation micromanipulators 7. The microelectrodes are preferably carbon fiber electrodes, and most preferably
20 carbon fiber ultramicroelectrodes (5 μm in diameter), or hollow glass fiber electrodes.

A voltage generator 8 is used to provide the required electrical field.

For fluorescence imaging and optical trapping, two
25 colinear laser beams are sent into the microscope objective 9. A 488-nm beam from an argon ion laser 10 (the beam from the argon ion laser is denoted by black, thin arrows) was used to excite fluorescein and a 992-nm beam from a MOPA diode laser 4 (the beam from the argon ion
30 laser is denoted by black, thick arrows) was used for optical trapping.

The resulting fluorescence and bright field images are directed to a CCD camera 11.

The setup also comprises mirrors 12, a dichroic
35 beamsplitter 13, a polychroic beamsplitter 14, a lens 15, a spinning disc 16, and a filter 17.

The method according to the invention is suitable for manipulating the genetic identity and biochemical surface properties of individual cellular or sub-cellular structures, such as organelles. It is especially suitable and interesting for *in vitro*-fertilization. It can also
5 be used in several other applications such as cloning, creation of hybridomas, manipulation of the composition of a cellular membrane, and delivery of a well-defined volume of a substance to a cell (particularly delivery of
10 a pharmaceutically active substance to a cell).

The method according to the invention is also suitable for electrofusion *in vivo* of patients or animals suffering from biochemical disruptions in individual groups of cells.

15 Many diseases, may they be genetically acquired or not, results in metabolic disruptions. For example, Parkinson's disease caused by degeneration of neurons in the Nigro-striatal pathway result in malfunctioning in the biochemical machinery for production of dopamine in an
20 isolated population of cells. This in turn results in motorbehavioral deficits. The standard treatment of Parkinson's disease is by oral administration of L-DOPA, a precursor of dopamine. Alternatively, grafted tissue with neuronal cells producing dopamine is transplanted into
25 the patient's brain. Intracellular drug or gene-administration *in vivo* into the appropriate brain structures can be accomplished using an electrofusion procedure similar to that described in the above examples and used as a therapeutic strategy.

30 Other diseases where a small population of cells are malfunctioning include many disorders in the inner organs, but also tumors.

Experimental treatment of brain tumors using genetically engineered viruses for gene delivery has been used with
35 anecdotal reports of success. However, the use of viruses as a delivery system has limitations in that it might pose a potential hazard should the virus mutate. Using an electrofu-

sion procedure for gene delivery (e.g. "suicide genes" cytokine deaminase or thymidine kinase) similar to that described in the examples below eliminates the need for the use of virus delivery systems in cancer therapy.

5 Many times a focal administration (administration directly to the malfunctioning set of cells) of drugs or genes (gene therapy) can be expected to be far superior than intraperitoneal, oral, intraventricular, or any other kind of commonly employed drug-administration technique. Intracellu-
10 lar drug-and-gene-administration *in vivo* can be accomplished using an electrofusion procedure similar to that described in the examples below. Because of the extremely small dimensions of the electrodes, in combination with the low voltages applied, very little tissue trauma is expected. Furthermore,
15 the positioning of the electrodes and the subsequent gene or drug delivery is very precise. This is especially important in the brain. It has been shown that microdialysis probes, which are on the order of a hundred times larger than the electrodes employed here for electroporation, cause very
20 little tissue trauma and disruption of local metabolism 24 hours after implantation.

For solute transfer into cells and organelles *in vivo* using electroporation it is preferred to use electrodes which are hollow. The fusion partner to be electrofused into cells
25 are then simply administered through the narrow channel in the center of the electrode by application of a flow by means of a syringe pump or a peristaltic pump or any other type of solution pumping system including electrophoresis.

An especially interesting possibility is to use battery-
30 operated perfusion/electroporation implants in bio-tolerable materials for continuous application of solutes with fusion partner for electrofusion into cells or tissue. Because such low potentials are required, batteries with emf's in the range of a few to 20 volts can be used. These battery-
35 operated electroporation units can be made small, virtually they can be included on a chip measuring only a few millimeters squared.

An example of an *in vivo* setup is shown in Fig. 5. A hollow electrode 20 is positioned by use of a stereotactic device close to a cell 21 in the brain. This cell 21 constitutes one of the fusion partners. The other fusion partner is constituted by liposomes containing a pharmaceutically active substance, such as DNA, a protein, RNA or a drug. The cell is perfused with the liposomes by injection of the second fusion partner into the electrode 21, either by use of a syringe 22 as shown in the figure, or by use some other appropriate means.

The invention will now be further explained in the following example. This example is only intended to illustrate the invention and should in no way be considered to limit the scope of the invention.

Examples

In the examples, the following methods and materials were used.

20 **Micromanipulation and fusion**

Optical trapping with highly focused laser beams was used to align the fusion partners. Using this procedure, one of the fusion partners (cell or liposome) in solution was trapped by an IR laser beam and brought into contact with the other fusion partner, which was either an adherent cell grown on a substratum or a cell placed on the substratum using, optical trapping with the set-up schematically shown in Fig. 1, and described above. For positioning of cells or liposomes close to cellular targets for fusion, the inventors also use reversible adsorption to carbon fiber microelectrode tips. In using this particular scheme for cell-liposome fusions, liposomes co-immobilized with cells on poly-L-lysine-coated glass surfaces are detached from the surface by pushing the electrode tip against the liposome roughly parallel to the object plane. The liposome will then adhere lightly to the electrode tip and can be relocated close

to a cellular structure by micromanipulators that can be moved in increments of 0.2 μm in three dimensions. This is shown in Figs. 2 A - C, where a liposome of about 5 μm in diameter is moved about 90 μm to a target cell, while
5 Figs. 2 D - G show how complex cell-liposomal patterns can be created using this simple approach. The liposomes in Figs. 2 A - C were first immobilized on poly-L-lysine-coated boro-silicate coverslips, and cells were added in suspension. A liposome could easily be moved over 90 μm
10 to a cell. One advantage of this technique over optical trapping is the much larger force that can be applied to the vesicles. The same method can be used for the alignment of two cells, with the exception that poly-L-lysine-coated coverglasses do not have to be used as the cells
15 in suspension simply attach to the surface due to gravity.

For electrofusion, the same pair of 5 μm -outer diameter carbon fiber microelectrodes is used. Fig. 1 depicts the geometrical arrangement of the electrodes with
20 respect to a pair of cells prealigned for fusion. For cell-cell, and cell-liposome fusion, highly focused electrical fields are applied using a low-voltage pulse-generator. An advantage of this set-up is that the electrodes are of cellular to subcellular dimensions, enabling
25 fusion of single cells in complex cellular networks grown on a substratum. At the same time, the highly focused electric field minimizes the risk for unwanted fusion or electroporation of surrounding cells.

30 Experimental protocol

Optical trapping, microscopy, and fluorescence imaging

The optical trapping and fluorescence imaging systems were built in-house. The optical trap was formed by sending the output from a single-mode MOPA laser diode
35 (Model SDL-5762-A6, SDL, Inc.) through a spatial filter (model 900, Newport) so that the output was then reflected off a near-IR mirror. The reflected laser light

was passed through a dichroic mirror, reflected from a polychroic mirror (Chroma Technology Corp.) that is placed in a microscope (Nikon Diaphot or Leica DM IRB), and subsequently brought to a diffraction-limited focus with a high-numerical aperture objective (100 x, NA 1.4 Nikon and 100 x, NA 1.3 Leica, respectively). Fluorescence excitation was achieved by sending the 488-nm output of an argon ion laser (Spectra Physics 2025-05) through a telescope followed by a spinning disc. The purpose of the spinning disc is to scatter the laser light so that uniform illumination is achieved for fluorescence imaging. The scattered laser light from the disk was collected by a lens and reflected from a dichroic mirror (Chroma Technology Corp). This reflected light was sent into the microscope and was reflected by a polychroic mirror. Fluorescence and brightfield imaging was performed by a 3-chip color CCD-camera (Hamamatsu) or a silicon-intensified target camera (Hamamatsu) and recorded by a Super VHS recorder (Panasonic) or dumped directly to a hard disk via a frame grabber.

Electrofusion instrumentation

For electrofusion experiments, cell dishes were mounted in a circular polycarbonate holder using vacuum grease, and transferred to the stage of an inverted microscope. Two carbon fiber microelectrodes (Axon Instruments, Inc. ProCFE) with an outer diameter of 5 μm were positioned close at each side of the respective fusion partner by high-graduation micromanipulators (Narishige MWH-3). The two carbon fiber electrode tips (anode and cathode) were positioned at an angle of 0-20°, and 160-180° with respect to the object plane. Cells were fused with multiple 1-ms pulses, using a pulse generator (Digitimer Stimulator DS9A) or a homebuilt variant. The voltage output from the pulsegenerator was calibrated using high-impedance electrodes and a patch-clamp amplifier.

The electrofusion buffer was either a 0.3 mol/kg Hanks Hepes solution (137 mM NaCl, 5.4 mM KCl, 0.41 mM MgSO₄, 0.4 mM MgCl₂, 1.26 mM CaCl₂, 0.64 mM KH₂PO₄, 3.0 mM NaHCO₃, 5.5 mM D-glucose, 20 mM Hepes, pH adjusted to 7.4 with NaOH) or a 0.2 mol/kg Hepes Saline buffer (135 mM NaCl, 5 mM KCl, 10 mM glucose, 2 mM MgCl₂, 2 mM CaCl₂ and 10 mM HEPES) diluted with 30-50% MilliQ-water. For PC12 cells were standard iso-osmolar and hypo-osmolar fusion media used, 300 L3 and 75 L3 receptively [Foung, S. et al, J of Immunol Methods, 134, 35-42].

For the NG-108 and Cos 7 cell-cell fusion experiments, 5% PEG 4000 was added to the fusion media, and in the cell-liposome fusions, 1.25% DMSO was added.

15 Cell culture

Jurkat, NG 108, COS 7, and PC12 cells were cultured according to standard procedures. The NG-108 and Cos 7 cells were treated with protease (from Aspergillus Oryaze) 2mg/ml, for 5-30 min in incubator (37 degrees Celsius, 90% humidity and 5% CO₂ atmosphere).

Preparation of fluorescein-encapsulated unilamellar vesicles and fluorescently labeled proteoliposomes

Liposomes from L- α -phosphatidylcholine in chloroform (powder from fresh egg yolk, Sigma St. Louis, MO) were obtained in high yield using a rotary evaporation method [as described e.g. in Moscho, A., et al., 1996, Rapid preparation of giant unilamellar vesicles, Proc. Natl. Acad. Sci. USA 93: 11443-11445]. Fluorescently labeled γ -GT was prepared by reacting with 2.3 mM fluorescein isothiocyanate (FITC). Unreacted FITC was removed by running the γ -GT-FITC solution through an Econopac 10DG column (BioRad Laboratories, CA), with a 6000 D cut-off. Labeled γ -GT was then incorporated into the vesicle during the vesicle formation process.

Preparation of poly-L-lysine-coated cover slips

Cover-slips (borosilicate, 28 mm in diameter, 0,13 - 0,17mm thick, Kebo, Sweden) were washed in 70% ethanol/water solution (v/v), followed by MilliQ-water. The
5 glasses were placed in a poly-L-lysine (Sigma-Aldrich Europe)/MQ-water solution (0,1% (w/v)). Cover slips were mounted in a circular polycarbonate holder using vacuum grease. 1 ml of liposome solution was added. After 30
10 minutes a sufficient number of liposomes were immobilized, and the outside solution could be changed and cells added.

Micromanipulation of liposomes and cells using microelectrodes

15 For translation of liposomes to different locations on poly-L-lysine-coated borosilicate surfaces, carbon fiber microelectrodes controlled by high-graduation micromanipulators (Narishige, Japan, 0.2 μm resolution) were used simply by using a combined pushing/scraping movement
20 to loosen the vesicles from the surface. After the vesicles were detached from the surface, they adhered to the electrode tip and could be moved over long distances and be launched close to a cellular target. To determine whether significant loss of the liposomal content is a
25 result of this handling, liposomes were primed with fluorescein (10 μM), attached to the cover slips and washed thoroughly so the fluorescence background was significantly reduced. Comparison between the intravesicular
30 fluorescence intensity before and after moving the vesicles did not show signs of substantial loss of content (data not shown).

Chemicals and materials

Hepes (>99%), sodium chloride, potassium chloride,
35 and sodium hydroxide (all Suprapur), calcium dichloride, magnesium dichloride, magnesium sulfate, potassium dihydrogen phosphate, PEG 4000 and sodium hydrocarbonate,

were purchased from Merck. D-glucose (AnalaR) was from BDH Limited Poole and fluorescein (GC-grade), γ -GT, Protease (type XXIII, from *Aspergillus oryzae*), fluorescein (sodium salt), and DMSO were obtained from Sigma-Aldrich, Sweden. Fluorescein isothiocyanate was from Molecular Probes, Europe. Deionized water from a Milli-Q system (Millipore) was used.

Example 1 - cell-cell fusion

10 In this example two PC 12 cells (≈ 8 and $10 \mu\text{m}$ in diameter) brought into contact by optical trapping and immobilized on a cover slip were fused, as shown in Figs. 3 A - D. Fig. 3 A shows PC12 cells during dielectrophoresis (0.3 - 3 kV/cm, 2 MHz). Fig. 3 B illustrates initiation
15 of the fusion by the last fusion pulse (6 pulses of 1 ms duration per each, 3 kV/cm), this can be seen by a broader and flatter contact zone between the cells. Fig. 3 C (~ 1 minute after the fusion pulses) and Fig. 3 D (~ 2 minutes after the fusion pulses) show the subsequent
20 broadening of the fusion area between the cells, indicating complete fusion.

To demonstrate the high spatial resolution achieved with this technique, individual NG 108 cells in a network were fused (data not shown). In addition to PC 12 cells,
25 and NG 108 cells, Jurkat cells, and Cos 7 cells, were successfully fused (data not shown). Hybrid cells between PC12 cells and NG 108 cells were successfully created in similar fusion protocols (data not shown).

Because of the presence of cytoskeleton, fused cells
30 take much longer to reorganize its membrane and become spherical compared to liposomes. For example, typical liposome-liposome fusion, using an identical experimental set-up, is in the milliseconds regime (data not shown). For some cells with extensive cytoskeletal scaffolding,
35 membrane reorganization can take minutes. However, fusion as characterized by the initial cytoplasmic continuity still occurs within a second. It was generally observed

that fusion of cells pre-electroporated in a 0.2 mol/kg buffer were much faster than the fusion of cells held in an isotonic 0.3 mol/kg buffer. The fusion process from initial cytoplasmic continuity to totally fused cells in an isotonic media took several hours. This is consistent with earlier accounts on the fusion media's impact on membrane fusion events, like exocytosis [as described e.g. in Weber, G. et al., 1992, Manipulation of cells, organelles, and genomes by laser microbeam and optical trap, Int. Rev. Cyt., 133: 1-41] and cell-cell fusion [as described e.g. in Zimmerberg, J., et al., 1980, Micromolar Ca^{2+} stimulates fusion of lipid vesicles with planar bilayers containing a calcium-binding protein, Science, 210, 906-908; Scmitt, J. J., et al., 1989, Enhanced hybridoma production by electrofusion in strongly hypo-osmolar solutions, Biochim. Biophys. Acta, 983, 42-50; Scmitt, J. J., et al., 1989, Electrofusion of osmotically treated cells. Naturwissenschaften, 76, 122-123]. Lately it has been argued that the electrofusion enhancement reached by hypo-osmotic fusion media is due to spectrin denaturation [as described e.g. in Zimmermann, U., et al., 1990, Efficient hybridization of mouse-human cell lines by means of hypo-osmolar electrofusion, Journal of Immunological Methods, 134, 43-50; Chernomordik, L. V., et al., 1991, Evidence that the spectrin network and a nonosmotic force control the fusion product morphology in electrofused erythrocyte ghosts, Biophys. J., 60, 1026-1037].

In all NG-108 and Cos 7 fusion experiments, the cells were treated with protease (5-30 min), and for the NG-108 cells the cell fusion media contained 5% (w/v) PEG 4000 [as described e.g. in Sowers, A. E., 1995, Membrane skeleton restraint of surface shape change during fusion of erythrocyte membranes: evidence from use of osmotic and dielectrophoretic microforces as probes, Biophys. J., 69, 2507-2516]. The requirement of different pre-treatment and fusion conditions for the respective cell-

lines are in agreement with previous observations for cell fusion.

It is well-established that electrically fused cells are biologically intact and continue to grow. Also in our fusion protocol, cells adhered to surfaces and continued to grow when inspected five-to-twentyfour hours post-fusion.

Example 2 - cell-liposome fusion

Previous accounts of cell fusion have demonstrated that in addition to mammalian cells of other phenotypes, synthetic vesicles, as well as plant protoplasts can be fused to mammalian cells. Synthetic vesicles have been fused with cells using some kind of chemical treatment or such, for example PEG [as described, for example, in Stoicheva, N. G., et al., 1994, Electrically Induced fusion of mammalian cells in the presence of polyethylene glycol, J. Membr. Biol., 140: 177-182] or by using HVJ-glycoprotein-reconstituted liposomes [as described in Seibicke, S., et al., 1988, Fusion of lipid vesicles with ascites tumor cells and their lipid-depleted variants, Studies with radioactive- and fluorescent-labeled vesicles, Biochim. Biophys Acta, 944, 487-496]. Synthetic lipid-films have been incorporated in the plasma membrane in cells, and micro-injection facilitated, by gentle contact between a lipid-coated glass micropipette and the cellular membrane [as described e.g. in Laffafian, I., et al., 1998, Lipid-assisted microinjection: introducing material into the cytosol and membranes of small cells, Biophys. J., 75, 2558-2563]. Fusion schemes involving synthetic vesicles can be used for purposes of transferring cell-impermeant molecules into a target cell through mixing of contents and for transfer of membrane lipids and membrane associated structures, such as proteins, into the target cell membrane.

Figs. 4 A - E are two sequences of images that demonstrate single vesicle-cell fusion according to the inven-

tion. In the first sequence (Figs. 4 A - C) a $\approx 5 \mu\text{m}$ di-
 ameter phosphatidylcholine vesicle is fused with a $\approx 12 \mu\text{m}$
 diameter Cos-7 cell, and in the second sequence (Figs. 4
 D - E) a $\approx 3 \mu\text{m}$ diameter phosphatidylcholine vesicle with
 5 reconstituted γ -GT is fused with a $\approx 20 \mu\text{m}$ diameter NG-108
 cell (protease-treated for 30 min). This demonstrates the
 ability of introducing liposome-incorporated proteins
 into a cellular structure. It is noted that fusion of
 vesicles with cells was much more difficult to accomplish
 10 than fusion between two cells of the same type. Both ad-
 dition of DMSO ($\approx 2\%$) to 0.3 mol/kg fusion medium and use
 of 0.2 mol/kg fusion media were found to facilitate fu-
 sion. DMSO has been shown to facilitate both the uptake
 of DNA using electroporation and increases the yield of
 15 fusion, and the use of hypo-osmolar medium is well-known
 to increase the fusion yield of cells (see above). In the
 experiment shown in the figure, the fusions were per-
 formed in a HEPES-buffered saline solution, and 1.25% di-
 methylsulfoxide and 20% MQ-water was added to the exter-
 20 nal buffer solution to assist vesicle-cell electrofusion.

Example 3 - cell fusion using single open-bore fused sil-
 ica capillaries

Fusion experiments were performed with NG 108 cells,
 25 cultivated according to standard procedures and plated
 onto no. 1 circular cover slips, mounted in a circular
 polycarbonate holder and transferred to an inverted mi-
 croscope stage. During all experiments the cell-bath was
 grounded by a platinum wire. Cells were aligned for fu-
 30 sion using optical trapping. A high voltage power supply
 (Bertand, Hicksville, NY, USA) operated at positive po-
 tentials of 1-30 kV was used together with electrolyte-
 filled fused silica capillaries (30 cm long, $30 \mu\text{m}$ i.d.,
 $375 \mu\text{m}$ o.d.) employed as electrodes. The experimental
 35 setup was otherwise identical to that depicted in figure
 1. The fused silica electrodes were sharpened to an ap-
 proximate outer diameter of $50 \mu\text{m}$ by grinding the tip

WO 01/09297

PCT/SE00/01484

22

with a rotating sandpaper dish. The capillary and buffer container (that connects the inlet end of the capillary to the high-power voltage supply by a platinum wire) was filled with Hanks buffered saline. The sharpened capillary tip (outlet end) was positioned using high-graduation micromanipulators close to one of the fusion partners, typically, less than 10 μm . Fusion of two aligned NG108-15 cells was performed by applying pulses of 5-to-15 kV for 0.1-5 seconds.

10 It was demonstrated that this method according to the invention is highly efficient for fusion of two cells in a complex system. This is especially important for application in *in vivo* fusion of cells and other fusion partners.

CLAIMS

1. A method for selective electrofusion of at least two fusion partners having cell-like membranes, comprising the following steps:
- 5 A) the fusion partners are brought into contact with each other
- 10 B) at least one microelectrode is used to provide an electrical field of a strength sufficient to obtain fusion and highly focused on the fusion partners, wherein said at least one microelectrode is positioned by use of a microscope, at least one micropositioner and/or a stereotactic device.
- 15 2. A method according to claim 1, wherein only one microelectrode, sufficiently small to permit the selective fusion of two fusion partners, is used to provide the electrical field in step B.
- 20 3. A method according to claim 1, wherein two microelectrodes, sufficiently small to permit the selective fusion of two fusion partners, are used to provide the electrical field in step B.
- 25 4. A method according to claim 1 or 2, wherein one electrode movably mounted on a microchip is used to provide the electrical field in step B.
- 30 5. A method according to claim 1 or 3, wherein several electrodes movably mounted on a microchip are used to provide the electrical field in step B.
- 35 6. A method according to claim 4 or 5, wherein the electrode(s) is (are) movably mounted on a microchip of a suitable design for combinatorial synthesis of fusion products.
7. A method according to any one of the claims 2-6, wherein at least one microelectrode is hollow, and sufficiently small to permit the selective fusion of two fusion partners.
8. A method according to claim 2-7, wherein at least one microelectrode that is hollow, electrolyte-filled,

and sufficiently small to permit the selective fusion of two fusion partners, is used to provide the electrical field in step B, and said microelectrode is also used to deliver fusion partners or chemical agents by electroen-
5 doosmosis, electrophoresis, or by Poiseuille flow.

9. A method according to any one of the claims 2-8, wherein the outer diameter of said electrode(s) is sufficiently small to permit the selective fusion of said at least two fusion partners without affecting nearby struc-
10 tures, such as cells, liposomes, and proteoliposomes).

10. A method according to claim 9, wherein the outer diameter of said electrode(s) is 1-100 μm .

11. A method according to any one of the claims 2-10, wherein at least one electrode is used for delivery
15 of at least on fusion partner to the fusion site.

12. A method according to any one of the claims 2-11, wherein step A is performed by use of the electrodes.

13. A method according to any one of the claims 1-11, wherein step A is performed by use of optical trap-
20 ping.

14. A method according to any one of the claims 1-11, wherein step A is performed by use of micropipettes.

15. A method according to any one of the claims 1-14, wherein at least one of the fusion partners is a
25 cell, and the other fusion partner(s) independently is (are) selected from the group consisting of a single cell, a liposome, a proteoliposome, a synthetic vesicle, an egg cell, an enucleated egg cell, a sperm cell at any development stage and a plant protoplast.

30 16. A method according to any one of the claims 1-14, wherein at least one of the fusion partners is constituted by a multiple of a structure selected from the group consisting of a single cell, a liposome, a proteoliposome, a synthetic vesicle, an egg cell, an enucle-
35 ated egg cell, a sperm cell at any development stage and a plant protoplast.

17. A method according to any one of the claims 1-16, wherein the fusion partners are provided in a buffer prior to step B.

18. A method according to any one of the claims 1-5 17, wherein at least one of the fusion partners has been immobilized prior to step A.

19. A method according to any one of the claims 1-18, wherein one of the fusion partners is part of a cellular network.

10 20. A method according to any one of the claims 1-19, wherein at least one of the Fusion Partners has been electroporated in a buffer prior to step A.

21. A method according to any one of the claims 1-20, wherein at least one of the Fusion Partners has been 15 exposed to a dielectrophoretic field in a buffer prior to step A.

22. A method according to any one of the claims 1-21, wherein at least one of the Fusion Partners has been treated by a fusogenic or other agent that promotes close 20 cell-cell contacts.

23. Use of a method according to any one of the claims 1-22 in in vitro-fertilization.

24. Use of a method according to any one of the claims 1-22 in cloning, excluding human cloning.

25 25. Use of a method according to any one of the claims 1-22 for creation of hybridomas.

26. Use of a method according to any one of the claims 1-22 for manipulation of the composition of a cellular membrane.

30 27. Use of a method according to any one of the claims 1-22 for the delivery of a well-defined volume of a substance to a cell.

28. Use of a method according to any one of the claims 1-22 for the delivery of a pharmaceutically active 35 substance to a cell.

29. Use of a method according to any one of the claims 1-22 in treatment of a tumor.

24-09-2001

26

30. Use of a method according to any one of the claims 1-22 in treatment of chronic neurodegenerative diseases, such as Parkinson's disease and Alzheimer's disease.

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
8 February 2001 (08.02.2001)

PCT

(10) International Publication Number
WO 01/09297 A1

- (51) International Patent Classification⁷: C12N 13/00
- (21) International Application Number: PCT/SE00/01484
- (22) International Filing Date: 13 July 2000 (13.07.2000)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
9902817-7 30 July 1999 (30.07.1999) SE
- (71) Applicant (for all designated States except US): A+ SCIENCE INVEST AB [SE/SE]; Box 3096, S-400 10 Göteborg (SE).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): ORWAR, Owe [SE/SE]; Haga Kyrkogata 4, S-411 37 Göteborg (SE). ERIKSSON, Peter [SE/SE]; Dr. Sahléns gata 10, S-413 22 Göteborg (SE). CHIU, Daniel, T. [CA/US]; 7009 40th Avenue NE, Seattle, WA 98115 (US). MOSCHO, Alexander [DE/DE]; Volpimistrasse 27, D-80638 München (DE). ZARE, Richard, N. [US/US]; 724 Santa Ynez Street, Stanford, CA 94305 (US).
- (74) Agent: AWAPATENT AB; Box 11394, S-404 28 Göteborg (SE).
- (81) Designated States (national): AE, AG, AL, AM, AT, AT (utility model), AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ, CZ (utility model), DE, DE (utility model), DK, DK (utility model), DM, DZ, EE, EE (utility model), ES, FI, FI (utility model), GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KR (utility model), KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (utility model), SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).
- Published:**
- With international search report.
 - Before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments.
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: A METHOD FOR SELECTIVE ELECTROFUSION OF AT LEAST TWO FUSION PARTNERS HAVING CELL-LIKE MEMBRANES

(57) Abstract: Disclosed is a method for selective electrofusion of at least two fusion partners having cell-like membranes and cellular or subcellular dimensions, comprising the following steps: A) the fusion partners are brought into contact with each other and B) an electrical field of a strength sufficient to obtain fusion and highly focused on the fusion partners is applied. The fusion partners are independently selected from the group consisting of a single cell, a liposome, a proteoliposome, a synthetic vesicle, an egg cell, an enucleated egg cell, a sperm cell at any development stage and a plant protoplast.

WO 01/09297 A1




Fig. 1

2/5





Fig. 2

3/5

**Fig. 3**

4/5




Fig. 4

5/5




Fig. 5

COMBINED DECLARATION AND POWER OF ATTORNEY FOR UTILITY PATENT APPLICATION	Attorney's Docket No. 003300-896
<p>As a below-named inventor, I hereby declare that:</p> <p>My residence, post office address and citizenship are as stated below next to my name:</p> <p>I BELIEVE I AM THE ORIGINAL, FIRST AND SOLE INVENTOR (if only one name is listed below) OR AN ORIGINAL, FIRST AND JOINT INVENTOR (if more than one name is listed below) OF THE SUBJECT MATTER WHICH IS CLAIMED AND FOR WHICH A PATENT IS SOUGHT ON THE INVENTION ENTITLED:</p> <p><u>A METHOD FOR SELECTIVE ELECTROFUSION OF AT LEAST TWO FUSION</u></p> <p><u>PARTNERS HAVING CELL-LIKE MEMBRANES</u></p> <p>the specification of which</p> <p>(check one) <input type="checkbox"/> is attached hereto;</p> <p><input checked="" type="checkbox"/> was filed on <u>July 13, 2000</u> as</p> <p>Application No. <u>PCT/SE00/01484</u></p> <p>and was amended on _____ (if applicable)</p> <p>I HAVE REVIEWED AND UNDERSTAND THE CONTENTS OF THE ABOVE-IDENTIFIED SPECIFICATION, INCLUDING THE CLAIMS, AS AMENDED BY ANY AMENDMENT REFERRED TO ABOVE;</p> <p>I ACKNOWLEDGE THE DUTY TO DISCLOSE TO THE OFFICE ALL INFORMATION KNOWN TO ME TO BE MATERIAL TO PATENTABILITY AS DEFINED IN TITLE 37, CODE OF FEDERAL REGULATIONS, Sec. 1.56 (as amended effective March 16, 1992);</p> <p>I do not know and do not believe the said invention was ever known or used in the United States of America before my or our invention thereof, or patented or described in any printed publication in any country before my or our invention thereof or more than one year prior to said application; that said invention was not in public use or on sale in the United States of America more than one year prior to said application; that said invention has not been patented or made the subject of an inventor's certificate issued before the date of said application in any country foreign to the United States of America on any application filed by me or my legal representatives or assigns more than twelve months prior to said application;</p> <p>I hereby claim foreign priority benefits under Title 35, United States Code Sec. 119 and/or Sec. 363 of any foreign application(s) for patent or inventor's certificate as indicated below and have also identified below any foreign application for patent or inventor's certificate on this invention having a filing date before that of the application(s) on which priority is claimed:</p>	

COMBINED DECLARATION AND POWER OF ATTORNEY

Attorney's Docket No.

003300-896

COUNTRY/INTERNATIONAL	APPLICATION NUMBER	DATE OF FILING (day, month, year)	PRIORITY CLAIMED
Sweden	9902817-7	30 July 1999	YES <u>X</u> NO
			YES NO

I hereby appoint the following attorneys and agent(s) to prosecute said application and to transact all business in the Patent and Trademark Office connected therewith and to file, prosecute and to transact all business in connection with international applications directed to said invention:

William L. Mathis	17,337	Eric H. Weisblat	30,505	Bruce T. Wiedler	33,815
Robert S. Swicker	19,885	James W. Peterson	26,057	Todd R. Walters	34,040
Patton N. Mandros	22,174	Teresa Susanek Rea	30,427	Ronald S. Jilions	31,979
Edmon S. Duffett, Jr.	22,050	Robert E. Krebs	25,885	Harold R. Brown III	36,331
Norman H. Steppa	22,716	William C. Rowland	30,888	Allen R. Baum	26,086
Ronald L. Grudzinski	24,970	T. Gene Dillahunty	25,423	Brian P. O'Shaughnessy	32,747
Frederick G. Michaud, Jr.	26,003	Patrick C. Keane	32,858	Kenneth B. Lefler	36,075
Alan E. Kopacki	25,813	B. Jefferson Boggs, Jr.	32,344	Fred W. Hathaway	32,236
Regis E. Stinner	26,999	William H. Barz	25,952	Wendi L. Weinsela	34,456
Samuel C. Miller, III	27,360	Peter K. Skiff	31,917	Mary Ann Dillahunty	34,576
Robert G. Mubai	28,531	Richard J. McGrath	29,195	Donna M. Meuth	36,607
George A. Hovanoo, Jr.	28,223	Matthew L. Schneider	32,814	Mark R. Kregaloff	42,766
James A. LaBarre	28,632	Michael G. Savage	32,596		
E. Joseph Gess	28,510	Gerald F. Swiss	30,113		
R. Danny Huntington	27,903	Charles F. Wieland III	33,096		

21839

and: none

Address all correspondence to:



21839

Benton S. Duffett, Jr.
BURNS, DOANE, SWECKER & MATHIS, L.L.P.
P.O. Box 1404
Alexandria, Virginia 22313-1404

Address all telephone calls to: Benton S. Duffett, Jr. at (703) 836-6620.

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

FULL NAME OF SOLE OR FIRST INVENTOR

PETER ERIKSSON

SIGNATURE

DATE

RESIDENCE

Göteborg, Sweden

CITIZENSHIP

Sweden

POST OFFICE ADDRESS

Dr. Sahlfors gata 10, SE-413 22 Göteborg, Sweden

FULL NAME OF SECOND JOINT INVENTOR, IF ANY

DANIEL I. CHU

SIGNATURE

DATE

RESIDENCE

Seattle, Washington, U.S.A.

CITIZENSHIP

Canada

POST OFFICE ADDRESS

7009 40th Avenue NE, Seattle, Washington 98115, U.S.A.

01A1E0101

COMBINED DECLARATION AND POWER OF ATTORNEY		Attorney's Docket No. 003300-896	
FULL NAME OF THIRD JOINT INVENTOR, IF ANY ALEXANDER MOSCHO		SIGNATURE	
RESIDENCE München, Germany DEX		CITIZENSHIP Germany	
POST OFFICE ADDRESS Volpimstrasse 27, DE-80638 München, Germany			
FULL NAME OF FOURTH JOINT INVENTOR, IF ANY OWE ORWAR		SIGNATURE <i>Owe Orwar</i>	
RESIDENCE Hovås, Sweden SEX		CITIZENSHIP Sweden	
POST OFFICE ADDRESS Åskims Kyrkväg 6, SE-436 51 Hovås, Sweden			
FULL NAME OF FIFTH JOINT INVENTOR, IF ANY RICHARD N. ZARE		SIGNATURE <i>Richard N. Zare</i>	
RESIDENCE Stanford, California, U.S.A. CA		CITIZENSHIP U.S.A.	
POST OFFICE ADDRESS 724 South Yuez Street, Stanford, California 94305, U.S.A.			

COMBINED DECLARATION AND POWER OF ATTORNEY		Attorney's Docket No. 003300-896	
FULL NAME OF THIRD JOINT INVENTOR, IF ANY ALEXANDER MOSCHO		SIGNATURE <i>Alex Moscho</i>	DATE 15.06.02
RESIDENCE München, Germany		CITIZENSHIP Germany	
POST OFFICE ADDRESS WOLFRATSHANSENER STR. 27a Volpimbach 27, DE-80638 München, Germany ① - 02045 Pullach			
FULL NAME OF FOURTH JOINT INVENTOR, IF ANY OWE ORWAR		SIGNATURE	DATE
RESIDENCE Hovås, Sweden		CITIZENSHIP Sweden	
POST OFFICE ADDRESS Laskims Kyrkväg 6, SE-436 51 Hovås, Sweden			
FULL NAME OF FIFTH JOINT INVENTOR, IF ANY RICHARD N. ZARE		SIGNATURE	DATE
RESIDENCE Stanford, California, U.S.A.		CITIZENSHIP U.S.A.	
POST OFFICE ADDRESS 724 South Yocum Street, Stanford, California 94305, U.S.A.			